

Claim Amendments

1. (Currently amended) A gasket comprising:

a metal substrate disposed along an outer perimeter of the gasket;

an elastomeric bead disposed along at least a part of an interior perimeter of the metal substrate;

**an elastomeric ring disposed ~~along~~ around an opening of the metal substrate,
wherein the elastomeric ring has an inner diameter, wherein the opening has an
opening diameter, and wherein the inner diameter of the elastomeric ring is smaller
than the opening diameter of the opening;**

**wherein a fastener that is disposable within the opening has an outer diameter, and
wherein the inner diameter that is smaller than [[an]] the outer diameter of [[a]] the
fastener, such that the fastener is retained with the gasket when the fastener is inserted
in the elastomeric ring by radially compressing the elastomeric ring between the
fastener and the opening.**

2. (Original) The gasket of claim 1, wherein a plurality of teeth disposed along an outer perimeter of the elastomeric bead correspond with a plurality of grooves disposed along at least a section of the interior perimeter of the metal substrate.

3. (Original) The gasket of claim 1, wherein a plurality of teeth disposed along an outer perimeter of the elastomeric ring correspond with a plurality of grooves disposed along at least a segment of the interior perimeter of the metal substrate.

4. (Original) The gasket of claim 1, wherein the elastomeric bead and the elastomeric ring are formed of a continuous rubber material that is formed on the metal substrate.

5. (Cancelled).

6. (Original) The gasket of claim 1, wherein the gasket is capable of fitting to a flange having a fastener hole, such that when the fastener is inserted through the fastener hole and the elastomeric ring, the gasket and fastener are sufficiently attached to the flange to permit installation of the fastener without the gasket and fastener falling off the flange.

7. (Original) The gasket of claim 6, wherein the gasket is disposable between an engine cover and an oil pick-up tube attached to the flange.

8. (Currently amended) A gasket comprising:

a metal substrate disposed along an outer perimeter of the gasket, wherein the metal substrate has a plurality of grooves disposed along an interior perimeter of the metal substrate and an inner diameter of a fastener opening; wherein the fastener opening is arranged and constructed to accommodate a fastener having an outer shaft diameter, wherein the outer shaft diameter is smaller than the inner diameter of the fastener opening;

an elastomer comprising a bead ~~and a ring~~ disposed along an interior perimeter of the elastomeric seal and a ring disposed along the inner diameter of the fastener opening, wherein a plurality of teeth are formed along an outer perimeter of the elastomer, wherein the plurality of teeth are formed in the plurality of grooves, and wherein the ring has an inner diameter that is smaller than both the inner diameter of the fastener opening and the ~~the~~ outer shaft diameter of ~~the~~ fastener, such that the fastener is retained with the gasket when the fastener is inserted in the elastomeric ring.

9. (Original) The gasket of claim 8, further comprising a depression formed in the metal substrate.

10. (Original) The gasket of claim 8, wherein the gasket is capable of fitting to a flange having a fastener hole, such that when the fastener is inserted through the fastener

hole and the ring, the gasket and fastener are sufficiently attached to the flange to permit installation of the fastener without the gasket and fastener falling off the flange.

11. (Original) The gasket of claim 8, wherein the gasket is disposable between an engine cover and an oil pick-up tube attached to the flange.

12. (Previously presented) The gasket of claim 1, wherein the inner diameter of the elastomeric ring is smaller than an inner diameter of an opening formed the metal substrate into which opening the elastomeric ring extends.

13. (Currently amended) A gasket comprising:

a metal substrate disposed along an outer perimeter of the gasket, wherein the metal substrate has a plurality of grooves disposed along an interior perimeter of the metal substrate and along an inner diameter of a fastener opening, wherein the fastener opening is sized to cooperate with a specific fastener, such that the specific fastener has an outer shaft diameter, and the inner diameter of the fastener opening is larger than the outer shaft diameter;

an elastomeric bead comprising a plurality of teeth disposed along an outer perimeter of the elastomeric bead, wherein the elastomeric bead is disposed along the interior perimeter of the metal substrate, and wherein the plurality of teeth are disposed in some of the plurality of grooves;

a first elastomeric ring comprising at least two teeth disposed along an outer perimeter of the first elastomeric ring, wherein the first elastomeric ring is disposed in the fastener opening ~~along the interior perimeter~~ and near a first end of the metal substrate, wherein the at least two teeth are disposed in at least two of the plurality of grooves, and wherein the first elastomeric ring has an inner ring diameter that is smaller than ~~[[an]]the outer shaft diameter of a first fastener;~~

a second elastomeric ring comprising two or more teeth disposed along an outer perimeter of the second elastomeric ring, wherein the second elastomeric ring is disposed in an additional fastener opening that is ~~along the interior perimeter and near~~

a second end of the metal substrate, wherein the two or more teeth are disposed in two or more of the plurality of grooves, and wherein the second elastomeric ring has an additional inner ring diameter that is smaller than an additional outer shaft diameter of an additional~~second~~ fastener.

14. (Currently amended) The gasket of claim 13, wherein the elastomeric bead, the first elastomeric ring, and the second elastomeric ring, are formed of a continuous rubber material that is formed on the metal substrate.

15. (Original) The gasket of claim 13, further comprising a depression formed in the metal substrate.

16. (Currently amended) The gasket of claim 13, wherein the gasket is capable of fitting to a flange having a first fastener hole and a second fastener hole, such that when the first fastener is inserted through the first fastener hole and the first elastomeric ring and the ~~second~~ additional fastener is inserted through the second fastener hole and the second elastomeric ring, the gasket, the first fastener, and the ~~second~~ additional fastener are sufficiently attached to the flange to permit installation of the first fastener and the ~~second~~ additional fastener without the gasket and first fastener and the second additional fastener falling off the flange.

17. (Original) The gasket of claim 16, wherein the gasket is disposable between an engine cover and an oil pick-up tube attached to the flange.

18. (Currently amended) The gasket of claim 1, wherein the elastomeric ring extends radially inwardly of ~~[[an]]~~the opening in the metal substrate.

19. (Previously presented) The gasket of claim 1, wherein the inner diameter of the elastomeric ring forms an interference fit with the fastener.

20. (Previously presented) The gasket of claim 8, wherein the inner diameter of the ring forms an interference fit with the fastener.